

Product Sheet

Apollo ALA01 Pager

VHF: 19-21-0850 UHF: 19-21-0851

The Apollo ALA01 XL2000 is a rugged, top-read numeric pager featuring built-in synthesized crystal UHF and VHF frequencies, programmable manually on the device with password protection.



Product code
VHF: 19-21-0850
UHF: 19-21-0851

Key Features

- » Efficient communication with narrowband operation.
- » Versatile mounting options with display invert setting.
- » Enhanced clarity with holographically-enhanced LCD and dual backlights.
- » Secure attachment with a strong removable belt clip.
- » Simplified setup through hand programming mode.
- » Efficient messaging with customizable and pre-programmed phrases.
- » Reliable power from a single AA battery with lithium backup.
- » Rugged durability for demanding environments.
- » Custom compatibility to match your frequency or range requirements.
- » Wide applicability across various industries and applications.

Applications

Public Safety

- » Ideal for police, fire, and emergency services for reliable communication in critical situations.

Healthcare

- » Ensures efficient messaging for medical staff in hospitals and clinics.

Security Services

- » Reliable communication tool for security personnel in various settings.

Manufacturing

- » Suitable for coordination and messaging in factories and warehouses.

Transportation

- » Helps streamline communication in logistics and transportation companies.

Technical Specification

Apollo ALA01 Pager

VHF: 19-21-0850 UHF: 19-21-0851

| | |
|---------------------|------------------------------------|
| Frequency Range | VHF 135~174 MHz UHF 430~470 MHz |
| Bit rate | 512 / 1200 / 2400 bps for POCSAG |
| Channel Spacing | 25KHz |
| Code Format | POCSAG |
| Alert Tone Loudness | 85db @ 10 cm |
| Capcodes | 4 Capcodes |
| Battery | AA battery |
| Dimension | 49(L) x 74.5(W) x 32(H) mm |
| Weight | 76 g |

NB: All specifications and applications are indicative only and subject to change without prior notification.